

Evidence of Performance

Test of Thermally toughened soda lime silicate safety glass (TSG)

Test Report

No. 15-002314-PR02

(PB-H04-09-en-01)



Client
Gorica Staklo d.o.o.
Sisacka 43
10410 Velika Gorica
Croatia

Basis *)

EN 12150-1:2000-06
EN 12150-2:2004-10
EN 1288-1:2000-06
EN 1288-3:2000-06

Product
Thermally toughened soda lime silicate safety glass (TSG)

Designation TSG Float enamelled


Nominal thickness in mm 4, 5, 6, 8, 10, 12, 15, 19

Overall dimensions in mm 1100 x 360
(H x W)

Special features fine edged (grinded)

*) Correspond/s to the national standard/s (e.g. DIN EN)

Representation



Results
Test of toughened glass according to EN 12150-1:2000-06 and EN 1288-3:2006-06



Corresponds to the definition of toughened glass as per product standard EN 12150-2

Instructions for use

The results obtained can be used by the manufacturer for preparing the Declaration of Performance in accordance with the Construction Products Regulation 305/2011/EU. The provisions of the applicable product standard have to be observed.

Validity

The data and results given have been evaluated for the described test specimen; they will be valid for unchanged products as long as the above mentioned bases have not changed.

Notes on publication

The ift-Guidance Sheet "Conditions and Guidance for the Use of ift Test Documents" applies. The cover sheet can be used as abstract.

Contents

The report contains a total of 13 page/s.

ift Rosenheim

15.02.2016

Christian Neudecker
Deputy Head of Testing Department
Material Testing

Khalid El Harda, Dipl.-Ing. (FH)
Operating Testing Officer
Material Testing